

COMBINED SCREW AIR COMPRESSOR



The combined screw air compressor integrates the parts including screw compressor, freeze drier, fine filter and air tank, making it convenient for the user to install, use and move. After the air pass the integrated system, the quality of the air is made largely better to satisfy process requirements of various companies. It is of beautiful appearance, stable performance and economy. It is one of the important series exported by our company.

Model	Air delivery /Working pressure				Motor power		Cooling air /water volume	connect pipe diam.	air tank	Air dryer	Capacity	Precision filter	W.	Dimension(mm)		
	m ³ /min/bar													KW	m ³ /min	m ³
ERC-10SA	1.1/7	1.0/8	0.85/10	0.7/12.5	7.5	Y-Δ starting <3ppm	32.5	3/4"	0.5	ELH-10HA	1.5	END012	680	1650	730	1530
ERC-15SA	1.8/7	1.65/8	1.5/10	1.3/12.5	11		50	1"	0.5	ELH-15HA	2	END024	785	1955	800	1800
ERC-20SA	2.4/7	2.2/8	2.1/10	1.8/12.5	15		50	1"	0.5	ELH-20HA	2.5	END024	810	1955	800	1800
ERC-25SA	3.1/7	2.9/8	2.7/10	2.3/12.5	18.5		110	1"	0.5	ELH-30HA	3.8	END035	910	1900	1070	2012
ERC-30SA	3.8/7	3.6/8	3.2/10	2.5/12.5	22		110	1 1/2"	0.6	ELH-30HA	3.8	END035	930	1960	1070	2012
ERC-30SW	3.8/7	3.6/8	3.2/10	2.5/12.5	22		14.5	1 1/2"	0.6	ELH-30HA	3.8	END035	930	1960	1070	2012
72±5dB(A),testing according to the international GB/T4980-2003 standard																
Ambient temperature+15℃																
Voltage V/ HZ /PH : 380/50/3 220/60/3 440/50/3 etc or Two kinds of voltage reverse According to customer inquiry																