

HIGH PRESSURE SCREW AIR COMPRESSOR



MODEL	Compression Level	Air Delivery	Pressure	Motor Power	Oil Content	Outlet	Noise	Outlet	Weight	Dimension	
		(m ³ /min)	(MPa)	(kw)	(ppm)	Temp.	db(A)	Connection			KG
ERC-150UAL	Air cooling	single	11	1.7	110	3	a+15	75	DN50	3500	2500X1500X1900
ERC-175UAL		single	13	1.7	132	3	a+15	75	DN50	3500	2500X1500X1900
ERC-270UAL		single	22	1.7	200	3	a+15	75	DN65	4800	2850X1750X2000
ERC-330UAL		single	26	1.7	250	3	a+15	75	DN80	5450	3150X2000X2000
ERC-270UAL		Double	21	2	200	3	a+15	78	DN65	5000	2850X1750X2000
ERC-375UAL		Double	25	2.5	280	3	a+15	78	DN65	7000	4000X2000X2100
ERC-470UAL		Double	33	2.5	355	3	a+15	79	DN65	8000	4600X2300X2400
ERC-375UAL		Double	22.8	3	280	3	a+15	78	DN50	7000	4000X2000X2100
ERC-250UAL		Double	12.5	4	185	3	a+15	78	DN40	3780	2650X1600X1950
ERC-375UAL		Double	20	4	280	3	a+15	78	DN50	6000	4000X2000X2100

J.P.G TECHNOLOGIES