

## SCROLL AIR COMPRESSOR



Elang scroll air compressor is a unique design, the world today has become energy-saving compressor, scroll air compressor main moving vortex disk only tooth no war and tear, and longer service life, known as the free repair compressor. Scroll compressor stable movement, small vibration, working environment is halcyon, also known as the “super quiet compressor”.

### **Quality first**

ELANG compressor product quality fully reflects the most modern technology, its design and manufacturing processes are executed in accordance with the requirements of ISO9001 standard, the products meet environmental requirements, quality assurance, safety and reliability, long service life.

### **Space saving and environmental protection**

The products has compact structure, smaller size, with less occupation of the land, lower noise and vibration, it can be installed in any place where you need it, even in the production area can be used.

### **Easy installation and running simple**

When the compressor is delivered from the factory, the machine is filled with compressed oil. If the installation is in place, turn on the power, it will put into operation. LCD screen with backlight, clearly shows the operation state of the compressor.

### **Cost reduction and energy saving**

Using intelligent control system and fully automatic load/unload regulation can guarantee air compressor to run according to the demand of compressed air, reduce the operation cost and energy consumption.

Model	Rated power	Working Pressure	Air Delivery	No. of air end	Connection	Noise
	kW	bar	m3/min		Diameter	±3dB(A)
WAX-2.2/8	2.2	8/8.5	0.25	1	G1/2	46
WAX-2.2/10	2.2	10/10.5	0.2	1	G1/2	46
WAX-3.7/8	3.7	8/8.5	0.4	1	G1/2	48
WAX-5.5/8	5.5	8/8.5	0.6	1	G1/2	50
WAX-5.5/10	5.5	10/10.5	0.5	1	G1/2	50
WAX-7.7/8	7.7	8/8.5	0.88	2	G3/4	53
WAX-7.7/10	7.7	10/10.5	0.7	2	G3/4	53
WAX-11/8	11	8/8.5	1.2	2	G3/4	56
WAX-11/10	11	10/10.5	1	2	G3/4	56
WAX-16.5/8	16.5	8/8.5	1.7	3	G1	58
WAX-16.5/10	16.5	10/10.5	1.4	3	G1	58
WAX-18.7/8	18.7	8/8.5	2	4	G1/1/4	60
WAX-18.7/10	18.7	10/10.5	1.8	4	G1/1/4	60
WAX-22/8	22	8/8.5	2.5	4	G1/1/4	61
WAX-22/10	22	10/10.5	2.2	4	G1/1/4	61
WAX-30/8	29.7	8/8.5	3.25	6	G1/1/2	62
WAX-30/10	29.7	10/10.5	2.7	6	G1/1/2	62
WAX33/8	33	8/8.5	3.6	6	G1/1/2	63
WAX33/8	33	10/10.5	3	6	G1/1/2	63